



NOTES:

1. RIETSCHLE ZEPHYR, DRY, ROTARY CLAW VACUUM PUMPS AND COMPRESSORS ARE DESIGNED FOR CONTINUOUS OPERATION. REFER TO DATA SHEET DA 880 FOR DIMENSIONS AND PERFORMANCE CHARACTERISTICS.
2. THE SYSTEM IS PRE-WIRED AND PRE-PIPED FOR SINGLE POINT ELECTRICAL AND VACUUM CONNECTIONS.
3. ALL DIMENSIONS ARE TYPICAL AND SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT THE FACTORY TO CONFIRM CRITICAL DIMENSIONS.
4. WHEN INSTALLING THE SYSTEM, ALLOW ADEQUATE CLEARANCE FOR SERVICE ACCESS.

Model	Motor HP, each unit	Rcvr Vol gallons	L1 inches	L2 inches	W inches	H inches
Stack Mounted Simplex						
VRSS-100	3	240	66		62	103
VRSS-150	5	240	66		62	103
VRSS-250	7.5	240	66		62	103
VRSS-300	7.5	240	66		62	103
VRSS-400	10	240	66		62	103
VRSS-500	15	240	66		62	103
Stack Mounted Duplex						
VRSD-100	3	240	66	100	62	103
VRSD-150	5	240	66	100	62	103
VRSD-250	7.5	240	66	100	62	103
VRSD-300	7.5	240	66	100	62	103
VRSD-400	10	240	66	100	62	103
VRSD-500	15	240	66	100	62	103
Model						
	Motor HP, each unit	Rcvr Vol gallons	L1 inches	L2 inches	W inches	H inches
Stack Mounted Triplex / Quadruplex						
VRST / VRSQ-100	3	240		100	62	103
VRST / VRSQ-150	5	240		100	62	103
VRST / VRSQ-250	7.5	240		100	62	103
VRST / VRSQ-300	7.5	240		100	62	103
VRST / VRSQ-400	10	240		100	62	103
VRST / VRSQ-500	15	240		100	62	103

ZEPHYR