



NOTES:

1. RIETSCHLE VACFOX, OIL SEALED, ROTARY VANE VACUUM PUMPS ARE DESIGNED FOR CONTINUOUS OPERATION. REFER TO DATA SHEET DA 154 FOR DIMENSIONS AND PERFORMANCE CHARACTERISTICS.
2. THE SYSTEM IS PRE-WIRED AND PRE-PIPED FOR SINGLE POINT ELECTRICAL AND VACUUM CONNECTIONS.
3. ALL DIMENSIONS ARE TYPICAL AND SUBJECT TO CHANGE WITHOUT NOTICE. CONTACT THE FACTORY TO CONFIRM CRITICAL DIMENSIONS.
4. WHEN INSTALLING THE SYSTEM, ALLOW ADEQUATE CLEARANCE FOR SERVICE ACCESS.

Model	Motor HP, each unit	Rcvr Vol gallons	L inches	W inches	H inches
Tank Mounted Simplex					
VXTS-015	1	80	70	24	50
VXTS-025	1.5	80	70	24	50
VXTS-050	2	120	77	27	54
VXTS-075	3	120	80	27	60
VXTS-100	5	120	90	27	54
VXTS-150	5	120	90	27	54

Model	Motor HP, each unit	Rcvr Vol gallons	L inches	W inches	H inches
Tank Mounted Duplex					
VXTD-015	1	80	70	24	50
VXTD-025	1.5	80	70	24	50
VXTD-050	2	120	77	27	54
VXTD-075	3	120	80	27	60
VXTD-100	5	120	90	27	54
VXTD-150	5	120	90	27	54

VACFOX